





## Flight test report: EN 926-2:2013

Manufacturer	Axis Paragliding	Certification number		PG_0878.2014	
Address	Nove Sady 39 602 00 Brno Czech Republic	Date of flight test		22. 08. 2014	
Glider model	Venus 4 M	Classification		D	
Representative	Radek	Place of test		Villeneuve	
Trimmer	no				
Test pilot		Thurnheer Claude		Zoller Alain	
Harness		Supair - Altiplume S		Gin Gliders - Gingo 2 L	
Harness to risers distance (cm)		43		41	
Distance between r	• •	44		46	
Total weight in fligh	, ,	80		105	
rotal weight in high	it (kg)	00		103	
1. Inflation/Take-off		С			
Rising behaviour		Overshoots, shall be slowed down to avoid a front collapse	С	Overshoots, shall be slowed down to avoid a front collapse	С
Special take off technique	required	No	Α	No	Α
2. Landing		Α			
Special landing technique		No	Α	No	Α
3. Speed in straight fligh		В			
Trim speed more than 30		Yes	Α	Yes	Α
	ntrols larger than 10 km/h	Yes	Α	Yes	Α
Minimum speed		Less than 25 km/h	Α	25 km/h to 30 km/h	В
4. Control movement		С			
Max. weight in flight up	to 80 kg				
Symmetric control pressure / travel		not available	0	not available	0
Max. weight in flight 80	kg to 100 kg				
Symmetric control pressure / travel		Increasing / greater than 60 cm	Α	not available	0
Max. weight in flight gre	ater than 100 kg				
Symmetric control pressu		not available	0	Increasing / 50 cm to 65 cm	С
5. Pitch stability exiting		A			
Dive forward angle on exi	t	Dive forward less than 30°	Α	Dive forward less than 30°	Α
Collapse occurs		No	Α	No	Α
flight	ng controls during accelerated	A			
Collapse occurs	nin n	No	Α	No	Α
<ol><li>Roll stability and dam Oscillations</li></ol>	ping	A Reducing	۸	Podusing	۸
	rala	Reducing	Α	Reducing	Α
Stability in gentle spirals     Tendency to return to straight flight		A Spontaneous exit	Α	Spontaneous exit	Α
•	Illy developed spiral dive	D Spontaneous exit	^	Sportaneous exit	^
Initial response of glider (f		Immediate reduction of rate of	Α	Immediate reduction of rate of turn	Α
		turn	_	Town areas in	_
Tendency to return to stra		Turn remains constant (g force constant, rate of turn constant)	D	Turn remains constant (g force constant, rate of turn constant)	D
Turn angle to recover normal flight		With pilot action	D	With pilot action	D

10. Symmetric front collapse	D			
Approximately 30 % chord				
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Spontaneous in less than 3 s	Α	Recovery through pilot action in less than a further 3 s	D
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	Α	Dive forward 0° to 30° Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	Yes	D
At least 50% chord				
Entry	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Recovery	Recovery through pilot action in	D	Spontaneous in less than 3 s	Α
Dive forward angle on exit / Change of course	less than a further 3 s  Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	Yes	D
Ç				
With accelerator	D 1: 1 1 1 450		D 1: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	•
Entry	Rocking back less than 45°	A	Rocking back greater than 45°	С
Recovery	Spontaneous in 3 s to 5 s	В	Recovery through pilot action in less than a further 3 s	D
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	Yes	D
11. Exiting deep stall (parachutal stall)	A Van	۸	Van	^
Deep stall achieved	Yes	A	Yes	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course Cascade occurs	Changing course less than 45° No	A A	Changing course less than 45° No	A A
12. High angle of attack recovery	C	^	NO	^
Recovery	Spontaneous in 3 s to 5 s	С	Spontaneous in less than 3 s	Α
Cascade occurs	No	Α	No	Α
13. Recovery from a developed full stall	C			
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Collapse	No collapse	Α	No collapse	Α
Cascade occurs (other than collapses)	No	Α	No	Α
Rocking back	Less than 45°	Α	Greater than 45°	С
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse	С			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 0° to 15°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of	Α	No (or only a small number of	Α
	collapsed cells with a spontaneous reinflation)		collapsed cells with a spontaneous reinflation)	
Twist occurs	No	A	No	A
Cascade occurs	No No	A	No	A
Folding lines used	No	Α	No	Α
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 45° to 60°	С	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α

Total change of course	Less than 360°	Α	Less than 360°	٨
Total change of course				Α
Collapse on the opposite side occurs	Yes, no turn reversal	С	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	Not available	0	Yes	F
<b>G</b>				
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	Α	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	Yes	F
Ç				
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No	Α	Yes	F
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	Α			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency	A			
Spin occurs	No	Α	No	Α
18. Recovery from a developed spin	В			
Spin rotation angle after release	Stops spinning in 90° to 180°	В	Stops spinning in 90° to 180°	В
Cascade occurs	No	Α	No	Α
19. B-line stall	A			
Change of course before release	Changing course less than 45°	Α	Changing course less than 45°	Α
Behaviour before release	Remains stable with straight span	Α	Remains stable with straight span	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Cascade occurs	No	Α	No	Α
20. Big ears	С			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Unstable flight	С	Stable flight	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	•	Α	Dive forward 0° to 30°	Α
	Dive forward 0° to 30°			
21. Big ears in accelerated flight	C C			
		A	Dedicated controls	Α
21. Big ears in accelerated flight Entry procedure	С		Dedicated controls Stable flight	A A
21. Big ears in accelerated flight	C Dedicated controls	Α		

Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	Α	Stable flight	Α
22. Alternative means of directional control	Α			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0

24. Comments of test pilot

Comments