AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 🔺 CH-1844 Villeneuve 🔺 +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Flight test report: EN 926-2:2013+A1:2021* & NfL 2-565-20

•					
Manufacturer Davinci Products Inc.		Certification number	PG_1969.2022		
Address	53 sinchon-gil, Okcheon- myeon, Yangpyeong-gun 12505 Gyeonggi-do Republic of Korea	Flight test	1	18.05.2022	
Glider model	CLASSIC2 L	Classification	A		
Serial number	CLST-L42260-GD	Representative		None	
		Place of test		Villeneuve	
Trimmer	no	Place of lest	v	meneuve	
Folding lines used	no				
Test pilot		Claude Thurnheer	A	Anselm Rauh	
Harness		Advance - Success 4 M	S	Supair - Evo XC 3 L	
Harness to risers distance (cm)		44	4	44	
Distance between risers (cm)		44	4	48	
Total weight in fligh		90			
rotal weight in high	it (Kg)	90	I	120	
1. Inflation/Take-off		Α			
Rising behaviour		Smooth, easy and constant rising	А	Smooth, easy and constant rising	А
Special take off technique	required	No	А	No	А
2. Landing		Α			
Special landing technique required		No	A	No	A
3. Speed in straight flight		Α			
Trim speed more than 30 km/h		Yes		Yes	A
Speed range using the controls larger than 10 km/h		Yes	A	Yes	A
Minimum speed		Less than 25 km/h	A	Less than 25 km/h	A
4. Control movement		Α			
Max. weight in flight up to 80 kg			•		0
Symmetric control pressure / travel		not available	0	not available	0
Max. weight in flight 80 kg to 100 kg		In any particular theory (in any constant)	•	n et evelle ble	0
Symmetric control pressure / travel Max. weight in flight greater than 100 kg		Increasing / greater than 60 cm	A	not available	0
	-	not available	0	Increasing / greater than 65 am	٨
Symmetric control pressure / travel		A	0	Increasing / greater than 65 cm	A
5. Pitch stability exiting accelerated flight		A Dive forward less than 30°	۸	Dive forward less than 30°	А
Dive forward angle on exit Collapse occurs		No		No	A
•	ng controls during accelerated	A	~		~
Collapse occurs		No	А	No	А
7. Roll stability and dam	ping	Α			
Oscillations		Reducing	А	Reducing	А
8. Stability in gentle spin	rals	Α			
Tendency to return to stra	ight flight	Spontaneous exit	А	Spontaneous exit	А
9. Behaviour exiting a fu	Illy developed spiral dive	А			
Initial response of glider (first 180°)		Immediate reduction of rate of turn	А	Immediate reduction of rate of turn	А
Tendency to return to straight flight		Spontaneous exit (g force decreasing, rate of turn decreasing)	A	Spontaneous exit (g force decreasing, rate of turn decreasing)	A
Turn angle to recover normal flight		Less than 720°, spontaneous recovery	A	Less than 720°, spontaneous recovery	A
10. Symmetric front coll	apse	Α			
Approximately 30 % chord					
Entry		Rocking back less than 45°	A	Rocking back less than 45°	A

*This standard is NOT covered by accreditation D-IS-19457-01 Test Report generated automatically by AIR TURQUOISE SA, valid without signature Rev 07 | 04.03.2022 // ISO | 91.22 // Page 1 of 3

Deserves		•		•
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	A	Dive forward 0° to 30° Keeping course	A
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
At least 50% chord				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A		A
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
With accelerator				
Entry	Rocking back less than 45°	А	Rocking back less than 45°	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	A		A
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
11. Exiting deep stall (parachutal stall)	A		-	
Deep stall achieved	Yes	А	Yes	А
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No		No	A
12. High angle of attack recovery	A	А		~
Recovery	Spontaneous in less than 3 s	А	Spontaneous in less than 3 s	А
Cascade occurs	No	A	No	A
13. Recovery from a developed full stall	A	~	NO	~
Dive forward angle on exit	Dive forward 0° to 30°	А	Dive forward 0° to 30°	А
Collapse	No collapse	A	No collapse	A
•	No conapse	A	No collapse	
Cascade occurs (other than collapses)	Less than 45°	A	Less than 45°	A
Rocking back				A
Line tension	Most lines tight	A	Most lines tight	A
14. Asymmetric collapse	Α			
Small asymmetric collapse Change of course until re-inflation / Maximum dive forward or	Less than 00° / Dive or roll angle	۸	Lass than 00° / Dive or roll angle	^
roll angle	Less than 90° / Dive or roll angle 0° to 15°	A	Less than 90° / Dive or roll angle 0° to 15°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	А	Spontaneous re-inflation	А
Total change of course	Less than 360°	А	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	A	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	A	Spontaneous re-inflation	A

*This standard is NOT covered by accreditation D-IS-19457-01 Test Report generated automatically by AIR TURQUOISE SA, valid without signature Rev 07 | 04.03.2022 // ISO | 91.22 // Page 2 of 3

Total change of course	Less than 360°	A	Less than 360°	A
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	А	No	А
Cascade occurs	No	А	No	А
Folding lines used	No	А	No	А
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	Less than 90° / Dive or roll angle 15° to 45°	А	Less than 90° / Dive or roll angle 15° to 45°	A
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	А
Total change of course	Less than 360°	Α	Less than 360°	А
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	A	No (or only a small number of collapsed cells with a spontaneous reinflation)	A
Twist occurs	No	Α	No	А
Cascade occurs	No	Α	No	А
Folding lines used	No	Α	No	А
15. Directional control with a maintained asymmetric collapse	Α			
Able to keep course	Yes	А	Yes	А
180° turn away from the collapsed side possible in 10 s	Yes	А	Yes	А
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	A	More than 50 % of the symmetric control travel	A
16. Trim speed spin tendency	Α			
Spin occurs	No	А	No	А
17. Low speed spin tendency	Α			
Spin occurs	No	А	No	А
18. Recovery from a developed spin	Α			
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in less than 90°	А
Cascade occurs	No	Α	No	А
19. B-line stall	Α			
Change of course before release	Changing course less than 45°	A	Changing course less than 45°	А
Behaviour before release	Remains stable with straight span	A	Remains stable with straight span	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	А
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Cascade occurs	No	Α	No	А
20. Big ears	Α			
Entry procedure	Dedicated controls	Α	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
21. Big ears in accelerated flight	A			
Entry procedure	Dedicated controls	A	Dedicated controls	A
Behaviour during big ears	Stable flight	A	Stable flight	A
Recovery	Spontaneous in less than 3 s	A	Spontaneous in less than 3 s	A
Dive forward angle on exit	Dive forward 0° to 30°	A	Dive forward 0° to 30°	A
Behaviour immediately after releasing the accelerator while maintaining big ears	Stable flight	A	Stable flight	A
22. Alternative means of directional control	A	•	Vec	
180° turn achievable in 20 s	Yes	A	Yes	A
Stall or spin occurs	No	A	No	A
23. Any other flight procedure and/or configuration described in the user's manual	0 not evellable	0		0
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0
24. Comments of test pilot				